

## Premium Basswood - Technical

Premium Basswood PROPERTIES	SHUTTER CHARACTERISTICS		
Material	Basswood		
Application	Internal		
Louvre Shape	Elliptical		
Louvre Type (width) mm	64mm	89mm	115mm
Louvre Thickness mm	10.5		
Stile Width (mm) and Profile	51mm Beaded / 57mm Flat		
Stile Thickness mm	27.5mm		
Rail Thickness mm	22mm		
Tilt Rod	Clearview / Centre / Offset		
Max Panel Height mm	3000mm		
Mid Rail Required if greater than (mm)	1800mm		
Max Hinged Panel Width mm	860mm	960mm	960mm
Max Hinged Bi-Fold Width mm	450mm		
Max Track Bi-Fold Width mm	600mm		
Special Shapes Available (include extra charge)	Oval / Hexagon/ Octagon/ Triangle/ Square/ Round		
Frame Styles available	Decor Frame 2" / Z Frame Crown / Multi L Frame / Z Line / Decor Frame 3" / Sunline Z Frame / Sunline L		
Minimal Width	250		
Premium Basswood Colours Available	W101, W104, W106, W109. W116. W120, BLACK		
Premium Basswood Stains Available	S402, S403 S404, S506, S507, S601, S602, S605, S606		
Hinges Available (extra for Stainless Steel)	Non Mortise / Inside Outside Pivots		
Optional Extras	Track Sliding / Track Bi Fold / Pelnets / Side Boards and Bottom Boards for Sliding and Bi-Fold Bay Windows / Corner Windows / Fixed Panels / Solid Panels		
<p><b>Premium Basswood</b> timber shutters are made from Basswood. It is a lightweight timber with very straight, fine uniform texture and grain. Basswood machines, screws and glues well and can be sanded and stained to a smooth finish. These hardwood shutters have good dimensional stability when dry. Premium A grade basswood is specially selected for its stability, uniform colouring and resistance to warping.</p>			